



## Ordering Information

|            |                                       |
|------------|---------------------------------------|
| PX211WC-J6 | 11.6" Capacitive, Intel Celeron J6412 |
| PX211WR-J6 | 11.6" Resistive, Intel Celeron J6412  |

## Hardware

|                                            |
|--------------------------------------------|
| Intel Celeron J6412 (2.0GHz)               |
| J6412: 8GB RAM, 256GB Flash                |
| J6412: 2 x GbE RJ-45                       |
| 2 x RS232 (422/485 option)                 |
| WiFi 2.4G & 5G, BT 4.0, (SIM/GPS option)   |
| 2 x USB 2.0, 2 x USB 3.0                   |
| 1 x HDMI, 1 x VGA                          |
| 1 x Line-out/Mic-in, 2 x built-in Speakers |

## Display & Touch

|                                 |
|---------------------------------|
| 11.6" TFT-LCD, 1920x1080        |
| Brightness 300 (cd/m²)          |
| View angle 178/178 (H°/V°)      |
| Backlight Lifetime 50,000 hours |
| Contrast 1000:1                 |
| Capacitive/Resistive touch      |

## OS & Power

|                      |
|----------------------|
| Win 10 / Linux       |
| 12~24VDC, < 48 watts |

## Mechanical

|                                               |
|-----------------------------------------------|
| Dimension 328.3 (W) x 216.3 (H) x 60.0 (D) mm |
| Net weight 2.3 (Kgs)                          |
| Cut-out 314.4 (W) x 202.4 (H)                 |
| Panel Mount, VESA 75x75/100x100               |
| Aluminum front bezel and chassis (Black)      |

## Environmental

|                                                         |
|---------------------------------------------------------|
| IP65 Front                                              |
| Op. Temp -10°C ~ 50°C                                   |
| Storage Temp. -20°C ~ 70°C                              |
| 10% to 90% @ 40°C (non-condensing)                      |
| CE/FCC (EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3) |

