

PX2 Celeron series

X86Panel PC



- ☐ Windows OS on Intel Celeron J6412
- ☐ Wide screens: 7"/10.1"/11.6"/15.6"/17.3"/21.5" or
- ☐ 4:3 screens: 8"/10.4"/12"/15"/17"/19"
- ☐ Resistive or Capacitive touch screen
- ☐ WIFI, BT, 3G/4G supported
- ☐ Built-in Speaker & HDMI/VGA out
- ☐ Aluminum Front and Chassis
- ☐ Panel/VESA mount w/ IP65 Front
- ☐ Black Bezel & Frame

Technical Specification

Model	PX207W△-⊗	PX210W△-⊗	PX211W△-⊗	PX215W△-⊗	PX217W△-⊗	PX222W△-⊗	PX208S△-⊗	PX210S△-⊗	PX212S△-⊗	PX215S△-⊗	PX217S△-⊗	PX219S△-⊗
Type	Wide Screen						4:3 Screen					
Size	7" TFT	10.1" TFT	11.6" TFT	15.6" TFT	17.3" TFT	21.5" TFT	8" TFT	10.4" TFT	12" TFT	15" TFT	17" TFT	19" TFT
Resolution	1024x600	1280x800	1920x1080	1920x1080	1920x1080	1920x1080	1024x768	1024x768	1024x768	1024x768	1280x1024	1280x1024
Brightness	250 cd/m2	300 cd/m2	300 cd/m2	300 cd/m2	400 cd/m2	250 cd/m2	300 cd/m2	300 cd/m2	450 cd/m2	450 cd/m2	400 cd/m2	250 cd/m2
Backlight Lifetime	50,000 hr											
CPU ⊗	⊗=J6: IntelCeleron J6412 (2.0GHz)											
RAM/Storage	⊗=J6: 8G / 256G											
Touch Screen △	△ :Add C for Projected Capacitive Touch, R for Resistive Touch											
COMs	1 x RS232	2 x RS232 (422/485 option)					1 x RS232	2 x RS232 (422/485 option)				
Ethernet	2xGbE RJ-45											
USB	2 x USB 2.0, 2 x USB 3.0											
Wireless	WIFI 2.4G & 5G, Bluetooth BT 4.0, (SIM/GPS option)											
Audio	1 x Audio Out, 2 x build-in Speakers											
Video Output	1 x HDMI 1080P@60fps, 1 x VGA											
Power Input	12~24V, max. 48 watts											
Weight	1.9 Kgs	2.2 Kgs	2.3 Kgs	3.9 Kgs	4.8 Kgs	6.6 Kgs	1.9 Kgs	2.4 Kgs	2.8 Kgs	4.5 Kgs	4.7 Kgs	5.7 Kgs
Operating Temp.	-10~50℃											
Storage Temp.	-20~70℃											
Moisture	10% ~ 90% @40℃											
Construction	Aluminum front bezel and chassis (Black color)											
IP Rating	IP65 (Front)											
Mounting	Panel mount, VESA 75x75 / 100 x 100											
Dimension (mm) (WxHxD)	225x160.7 x59	283.7x186.2 x60	328.3x216.3 x60	405.3x254.6 x67	452x285 x70.5	537.4x328.8 x64.5	225.5x185 x64.5	277.9x225.3 x64.5	312.3x250.8 x62	366.1x290 x68	399.2x331.6 x64.5	438.6x363.6 x62
Cut-out(mm) (WxH)	210.9x146.5	269.8x172.3	314.4x202.4	391.2x242.2	434.8x267.8	520.2x311.6	211.3x170.8	263.7x211.1	298.3x236.8	351.8x275.8	383.3x321.4	421.4x346.4
CE/FCC	EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3											
System Support	Windows 10, Linux											