







Features

- TI ARM® Cortex™ A8, Sitaratm™ AM3352 (1GHz)
- 15.6" TFT 1366 x 768, 500 cd/m², 50,000 hours
- 19.2 ~ 28.8V, Isolated Power
- Aluminum IP65 front bezel and steel chassis
- Panel or VESA 100 mm x 100 mm mount
- ESD Protection : Level 4 (Contact Discharge 8KV, Air-Gap Discharge 15KV), Class A
- Suitable for industrial applications

Specifications

CPU	TI ARM® Cortex™-A8, Sitaratm™ AM3352 (1GHz)
Memory	512MB SDRAM
Storage	4GB eMMC
I/O	1 x USB 2.0 host Type A 1 x USB 2.0 device Type B 2 x RS232/422/485, COM1, COM2 1 x RS232/485, COM3 or CAN Bus (Option) 1 x 10/100 Mbit Ethernet Port or 2 x 10/100 Mbit (Option) 1 x SD Card Slot
Display	15.6" TFT, 1366 x 768 Luminance 500 (cd/m ²) View angle 160/150 (H°/V°) Backlight Lifetime 50,000 hours Contrast ratio 600:1
Touch Screen	5-wire resistive touch
Power	19.2 ~ 28.8V Isolated Power
Construction	Aluminum IP65 front bezel and steel chassis
Net Weight(Kgs)	5.8 Kg
Mounting	Panel or VESA 100 x 100 mount
Dimensions (mm)	408.8(W) x 260.9(H) x 50.6(D)
Operating Temp.	0°C ~ 50°C
Storage Temp.	-20°C ~ 60°C
Humidity	10% to 90% @ 40°C, (non-condensing)
ESD Protection	Level 4 (Contact Discharge 8KV, Air-Gap Discharge 15KV), Class A
Certification	CE/FCC (EN 61000-6-4, EN 61000-6-2)



Pericom AG

Moskau 314B CH 8262 Ramsen t 052 740 00 55
Waldstr. 7 D 78262 Gailingen t 07734 48 70 343

www.pericom.biz
info@pericom.biz