



## Ordering Information

PX211WC-J1	11.6" Capacitive, Intel Celeron J1900
PX211WR-J1	11.6" Resistive, Intel Celeron J1900
PX211WC-J4	11.6" Capacitive, Intel Celeron J4125
PX211WR-J4	11.6" Resistive, Intel Celeron J4125

### Hardware

Intel Celeron J1900 (2.0GHz), J4125 (2.0GHz)  
 8GB RAM, 64GB Flash  
 J1900: 1 x GbE RJ-45 (2xGbE option)  
 J4125: 2 x GbE RJ-45  
 2 x RS232 (422/485 option)  
 WiFi 2.4G & 5G, BT 4.0, (SIM/GPS option)  
 2 x USB 2.0, 2 x USB 3.0  
 1 x HDMI, 1 x VGA  
 1 x Line-out/Mic-in, 2 x built-in Speakers

### Mechanical

Dimension 328.3 (W) x 216.3 (H) x 60.0 (D) mm  
 Net weight 2.3 (Kgs)  
 Cut-out 314.4 (W) x 202.4 (H)  
 Panel Mount, VESA 75x75/100x100  
 Aluminum front bezel and chassis (Black)

### Display & Touch

11.6" TFT-LCD, 1920x1080  
 Brightness 300 (cd/m<sup>2</sup>)  
 View angle 178/178 (H°/V°)  
 Backlight Lifetime 50,000 hours  
 Contrast 1000:1  
 Capacitive/Resistive touch

### OS & Power

Win 10 / Linux  
 12~24VDC, < 48 watts

### Environmental

IP65 Front  
 Op. Temp -10°C ~ 50°C  
 Storage Temp. -20°C ~ 70°C  
 10% to 90% @ 40°C (non-condensing)  
 CE/FCC (EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3)

