



Ordering Information

| | |
|------------|---------------------------------------|
| PX215WC-J1 | 15.6" Capacitive, Intel Celeron J1900 |
| PX215WR-J1 | 15.6" Resistive, Intel Celeron J1900 |
| PX215WC-J4 | 15.6" Capacitive, Intel Celeron J4125 |
| PX215WR-J4 | 15.6" Resistive, Intel Celeron J4125 |

Hardware

Intel Celeron J1900 (2.0GHz), J4125 (2.0GHz)

8GB RAM, 64GB Flash

J1900: 1 x GbE RJ-45 (2xGbE option)
J4125: 2 x GbE RJ-45

2 x RS232 (422/485 option)

WiFi 2.4G & 5G, BT 4.0, (SIM/GPS option)

2 x USB 2.0, 2 x USB 3.0

1 x HDMI, 1 x VGA

1 x Line-out/Mic-in, 2 x built-in Speakers

Mechanical

Dimension 405.3 (W) x 254.6 (H) x 67.0 (D) mm

Net weight 3.9 (Kgs)

Cut-out 391.2 (W) x 242.2 (H)

Panel Mount, VESA 75x75/100x100

Aluminum front bezel and chassis (Black)

Display & Touch

15.6" TFT-LCD, 1920x1080

Brightness 300 (cd/m²)

View angle 160/145 (H°/V°)

Backlight Lifetime 50,000 hours

Contrast 800:1

Capacitive/Resistive touch

OS & Power

Win 10 / Linux

12~24VDC, < 48 watts

Environmental

IP65 Front

Op. Temp -10°C ~ 50°C

Storage Temp. -20°C ~ 70°C

10% to 90% @ 40°C (non-condensing)

CE/FCC (EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3)

